

IGEL UD2

THE POWERFUL COST-EFFECTIVE ENDPOINT DEVICE FOR CLOUD WORKSPACES

Combined with IGEL OS, UD2 is an economical and highly effective solution for the future workplace.





IGEL OS, and the IGEL "chain of trust" strengthen security from the endpoint all the way to your virtual and cloud workspaces.



Configurable connectivity options offer flexibility across a vast range of user scenarios.



Connect to a second monitor with 2K @ 60Hz resolution via Display Port 1.1a.



UD2 with IGEL OS = Maximum Productivity

IGEL OS.

IGEL OS integrates with 130+ technologies to easily fit into almost any user environment with a familiar, trouble-free workspace.

This ecosystem is continuously expanding through the IGEL Ready program.

IGEL UMS.

With easy, automated control from a single console, the IGEL Universal Management Suite (UMS) securely manages the UD3 and up to 300,000 IGEL-powered endpoints located on the corporate LAN or off.

Connect with IGEL

IGEL cultivates success for our customers. A selection of services, support, and training offerings and a vibrant online community of EUC experts empower our users to achieve the full capabilities of their IGEL solution.

vmware^{*}





TECHNICAL SPECIFICATION UD2

activated on IGEL UD2 endpoint devices
is modular by design and lean, read-only file system, does not store data on the endpoint.
IGEL OS 11
IGEL Universal Management Suite
Intel Atom® x5-E8000 Quad-Core 1.04 GHz (2.0 GHz Burst Frequency) or
Intel Celeron® N3160 Quad-Core 1.6 GHz (2.24GHz Burst Frequency) depending on availability.
4 GB (1x 4GB SO-DIMM DDR3L 1600 MHz) or 2 GB (1x 2GB SO-DIMM DDR3L 1600 MHz)
8 GB (4 GB in earlier configurations)
Intel™ HD Graphics
128-512 MB shared memory
2 x DisplayPort 1.1a
2560 x 1600 @ 60 Hz. Details on accelerated video decoding in manual on kb.igel.com
10/100/1000 Ethernet (RJ-45 connector)
Not available
Not available
2 x front
3 x back
1 x back
1 x optional, via USB-to-parallel adapter
1 x optional, via USB-to-serial adapter
1 x front. 3.5 mm/ 1/8-inch TRRS audio jack (line-in/ line-out/headset) Realtek ALC897 or Realtek ALC888S HD audio depending on availability.
1x back
155 mm x 57 mm x 183 mm with foot stand 147 mm x 37 mm x 176 mm without foot stand
0.71 kg with foot stand
0.68 kg without foot stand 1.04 kg with foot stand and external power adapter
Fanless convection
0 °C to 40 °C, 32 °F to 104 °F vertical operation. 0 °C to 35 °C, 32 °F to 95 °F vertical operation with VESA mount. 0 °C to 35 °C, 32 °F to 95 °F horizontal operation with optional rubber feet.
20% - 80% non-condensing
external, 100 - 240 V / 50 - 60 Hz
12 V / 3 A External Power Adapter Level VI, UL/IEC 62368-1 (A140-1120300N)
4 W (idle) / 0.5 W (sleep) / < 0.3 W (off) @230 V, 50 Hz
ENERGY Star valid in USA, Canada, Switzerland, Taiwan und Japan. For more information contact regulatory.compliance@igel.com.

CONNECT WITH IGEL

IGEL Community

IGEL Ready

IGEL Partner Program

IGEL Academy

SUPPORT & SERVICES

IGEL Advanced Services
Regulatory Compliance
Extend Hardware Warranty
UD2 on Knowledge Base



