

CALMO Panel

VESA | ThinClient



10-Finger
Multitouch



disinfectable



Use with gloves




Further data

Technical data

OS	<ul style="list-style-type: none"> • Windows 10 Pro / IoT • IGEL Ready (OS11) • Linux 64-bit
CPU	<ul style="list-style-type: none"> • Intel® Celeron J4005, 2x 2,7 GHz • Intel® Pentium Silver J5005, 4x 2,8GHz
RAM	1x SO-DIMM DDR4 PC2400, max. 16 GB
Storage	1x 2,5" SSD
Display Size	10,1" - 23,8" 16:9 1920x1080 Pixels
Brightness/ contrast	10,1": 350 cd/m ² 1000:1 15,6": 400 cd/m ² 700:1 21,5": 250 cd/m ² 3000:1 23,8": 250 cd/m ² 1000:1
Touchdisplay	PCAP TFT Touchscreen with 3mm Safety Glass and LED Backlight
Graphics	Intel® UHD 600/605
Display Interface 1	DisplayPort 1.2 (4096 x 2160 @ 60Hz)
Display Interface 2	DisplayPort 1.2 (4096 x 2160 @ 60Hz)
Audio	Realtek ALC671 – 7.1 HD Audio
LAN	2x RJ45 @ 10/100/1000 Mbit/s (Intel® i210 + Realtek RTL8111G)
PSU	: 8–24V DC Direct input

interfaces

Rear bottom	4x USB, 2x DP, 2x LAN, DC-In, Terminal-In
Rear Top (10,1")	2x USB 3.1, Audio-In, Audio-Out



Size	10,1": 268 x 186 x 50 mm 15,6": 396 x 244 x 59 mm 21,5": 526 x 323 x 63 mm 23,8": 586 x 355 x 75 mm
Weight	3-10kg
Protection	IP65 Front, IP50 Rear Protected against cleanser (pH 2-11)
Temperature	-5 °C bis 50 °C
Special Features	<ul style="list-style-type: none"> • Always-On • Wake-on-LAN • PXE-Boot • TPM 2.0 • Watchdog • System Guard • Recovery-BIOS
Optional Extensions	<ul style="list-style-type: none"> • WiFi 6 incl. Bluetooth 5.0 • M.2 2242/2260/2280 Interface-Modules • 2x USB 3.1 • Bumper • Internal PSU • RS-232 • Dock with BC NFC RFID COM USB • PoE ++
Warranty	2 Years Bring-In (up to 5 Years)
Availability	Until 2025



For further information please visit:
www.calmo-pc.de