

SEAL GLOW 2™ WATERPROOF KEYBOARD

Model: S106G2, SW106G2

Seal Glow 2™ Waterproof Keyboards from Seal Shield have a 100% waterproof & dishwasher-safe rating that is IP68-certified and designed to withstand industrial-grade disinfectants & cleaners. LED backlit characters provide non-intrusive visibility assistance & location in darker settings with a full-size numeric keypad for easy entry of numbers. Laser-etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning. Features a Gold-Plated USB Quick Connect™ cable for easy plug-and-play.

FEATURES:



100% Waterproof,
Dishwasher-Safe,
& Fully Submersible



Gold Coated USB
Quick Connect Cable
with Seal Cap™ USB
Protector



Full-Size Numeric
Keypad and
Laser Etched Keycaps



LED Backlit Illuminated
Characters



Designed to Withstand
Industrial-Grade
Disinfectants & Cleaners



UV Reinforced Key
Caps



Fully Sealed Silicone
Keyboard is IP68-Certified



Compact Footprint



S106G2



SW106G2

ADVANCED CLEANING CAPABILITIES

- Dishwasher-Safe
- Compatible with Spray & Wipe Disinfectant Products:
 - Clorox Healthcare®
 - Lysol®
 - PDI Products
 - Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants



SEAL GLOW 2™ WATERPROOF KEYBOARD

Model: S106G2, SW106G2

TECHNICAL DATA:

| | |
|-------------------------------|---|
| Compatibility: | Windows® |
| Key Layout: | 103 US Language |
| Net Dimensions: | 15.15 x 5.43 x 0.78 in (38.5 x 13.8 x 2 cm) |
| Net Weight: | 1.02 lbs (0.465 kg) |
| Net Weight: | 1.28 lbs (0.585 kg) |
| Cable Length: | 6in(15cm) Quick Connect™ with USB Extension Cable |
| Connection Type: | Gold Plated USB |
| Key Switch Type: | Carbon point activation with Tactile Feedback |
| Key Switch Force: | 150 ±15 gf |
| Key Switch Life Cycle: | Greater than 10 Million keystrokes |
| Keycaps Imaging Type: | Laser Etched |
| Power Consumption: | 70mA Maximum (with LED lights ON) |
| Total Key Travel: | 0.063 ± 0.0196 in (1.6 ± 0.5 mm) |
| Operating Voltage: | 5VDC |
| Operating Voltage: | 100mA |
| Storage Temperature: | -5° - 140° F (-20° to 60° C) |
| EMI - RFI: | Conforms to FCC Rules for Class B Device |
| Waterproof/Dustproof Ratings: | IP68, NEMA 4X |
| Approvals/Certifications: | RoHS, WEEE, CE, FCC, ICE-003, RCM, REACH, WHQL, Cal Prop 65 |



Copyright© 2022, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty